

BK Technologies

KNG P25 Mobile Radio



Public Safety Communications

The KNG Series radio offers exceptional performance in a lightweight form. With industry leading RF and electrical specifications in a rugged, submersible housing, the KNG Series platform provides the performance needed for the most demanding applications making this the perfect radio for all aspects of government, public safety and first responder missions.

- ✓ P25 Trunking Option
- ✓ TDMA Phase II Compatible
- ✓ IP54 Water and Dust Protection
- ✓ USB PC Programmable
- ✓ NIST-Certified AES, FIPS 104-2, Level 2, & DES/OFB/CFB/XL
- ✓ MIL-STD 810 C/D/E/F/G
- ✓ Cloning to KNG & Legacy Series

	KNG Mobile Radio	KNG Remote Control Head (KAA0660)
Display	Alpha-numeric Touch Screen Display The KNG Mobile's innovative color TFT touch screen display solves many issues seen in existing mobile radio control heads. Day or night, get all the information you need right at your fingertips.	
Channel Capacity	5000	5000
Memory	64 MB Volatile 256 MB Non-Volatile (Flash)	64 MB Volatile 256 MB Non-Volatile (Flash)
VHF	KNG-M150	Compatible
UHF Range 1	KNG-M400	Compatible
UHF Range 2	KNG-M500	Compatible
700/800 MHz	KNG-M800	Compatible

Power and Current Drain

Power Supply	13.8 V DC ±20% Negative Ground
Transient Protection	Per EIA-374-A
Standby Current @ 13.8 V	0.15A All models
Receive Current Rated Audio @ 13.8 V	2.5A All Models
Transmit Current @ Rated Power	VHF (50 W) 15A, VHF(110 W) 22A, UHF (50W) 15A, 700/800 MHz 10 A

HCH - Handheld Control Head





Some Key Benefits

► Innovative Touch Screen Display

Touch screen display provides unparalleled level of end-user customizing, ease of use, and expansion as new technologies are integrated with Project 25 Standards

► Enhanced Voice Quality

The KNG Series radio uses the Third Generation Enhanced IMBE Project 25 dual rate Vocoder (AMBE+2 V1.80) for robust performance in noisy environments. Software based noise cancellation preserves situational awareness lost with dual microphone systems.

► 5 Line Color Bitmap Display

Status Icons, three customizable display lines of 14 characters and soft key legends.

► Environmental Reliability

Designed and tested to MIL-STD-810 and IP-54 rated.

► DHS P25 CAP Approved

DHS P25 Compliance Assessment Program Tested and Approved Public Safety Grade (TIA Class A).

► Robust Receiver

Improved range and less susceptibility to interference.

► Simulcast Operation

C4FM and CQPSK modes for robust performance in simulcast (including LSM) systems.

► Conventional Signaling

Analog MDC-1200 and digital APCO Project 25 for conventional operation.

► IP54

Water and dust protection

► Scan Modes

Dual priority scan, trunked priority scan, and dual mode scan

► NIST FIPS-140-2 Certification

The KNG Series radios employ a NIST Certified Cryptographic module.

► Multi-key/Multi-Algorithm

Multi-Key/Multi-Algorithm Encryption and Over-the-Air Rekey

► Encryption Key Fill

TIA-102-AACD compliant and interoperable with commercially available keyfill devices.

► Project 25 9600 Baud Trunking

The KNG Series radio operates on 9600 baud P25 Compliant Trunking Systems and has been Project 25 Compliance Assessment Program (P25CAP) tested and proven interoperable.

► OTAP

KNG Series radios support Over-the-Air Programming (OTAP) for operational efficiency.

► TDMA Phase 2

KNG Series 700/800 MHz platforms are Project 25 Phase 2 (TDMA) ready supporting double the voice capacity of Phase 1 trunking systems.

► Radio Authentication

Project 25 Radio Authentication per TIA-102-AACE-A is supported.

► GPS/Location Services

Project 25 Location Services per TIA-102-BAJB are supported.

► Room to Grow

Currently uses less than 20% of available memory and processor cycles.

Mobile Radio Options

The KNG platform meets today's demanding mission critical voice requirements is future ready and able to expand with changing standards and mission requirements.

- **KZA0154** Option, High Power, 110W
- **KAA0660** Remote Control Head
- **KAA0670** Handheld Control Head
- **KAA/KZA0569** P25 9600 Baud Trunking
- **KZA0576** DES-OFB/DES-CFB/DES-XL
- **KAA/KZA0580** AES Encryption FIPS-140-2, Level 2
- **KAA/KZA0583** P25 Over the Air Rekeying (OTAR)
- **KAA/KZA0583** Multi-Cast Vote Scan Plus

- **KAA/KZA0589** GPS Option for KNG Mobiles
- **KAA/KZA0592** Over the Air Reprogramming
- **KAA/KZA0594** P25 Phase II – 2 Slot TDMA Operation
- **KAA/KZA0596** P25 Radio Authentication
- **KAA0261** External Speaker 20W, 4 Ohm
- **KAA0276** Standard Handheld Microphone KNG-M
- **KAA0290** Handheld Programming Microphone

	700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776, 793-806 MHz 806-824,851-870 MHz	136-174 MHz	380-470 MHz 440-520 MHz
Channel Spacing		25/12.5 KHz	30/25/12.5 KHz	25/12.5 KHz 25/12.5 KHz
Maximum Frequency Separation		Full Band	Full Band	Full Band Full Band
Audio Output Power at Rated		500 mW	500 mW	500 mW 500 mW
Frequency Stability (-30°C to +60°C, +25°C Reference)		±.00015%	±.00015%	±.00015% ±.00015%
Analog Sensitivity	12dB SINAD	0.25µV	0.20µV	0.25µV 0.25µV
Digital Sensitivity	1% BER 5% BER	0.32µV 0.25 µV	0.27µV 0.20 µV	0.32µV 0.25 µV 0.32µV
Selectivity	25 KHz 12.5 KHz	75 dB 67 dB	80 dB 70 dB	78 dB 67 dB 77 dB 67 dB
Intermediation		-75 dB	-78 dB	-75 dB -75 dB
Spurious Rejection		-75 dB	-80 dB	-80 dB -80 dB
FM Hum and Noise	25 KHz 12.5 KHz	-50 dB -44 dB	-50 dB -44 dB	-50 dB -44 dB -50 dB -44 dB
Audio Distortion @ 15 Watts		3%	3%	3% 3%

Transmitter - Minimum Performance Specifications

	700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776, 793-806 MHz 806-824,851-870 MHz	136-174 MHz	380-470 MHz 440-520 MHz
Channel Spacing		25/12.5 KHz	30/25/12.5 KHz	25/12.5 KHz 25/12.5 KHz
Maximum Frequency Separation		Full Band	Full Band	Full Band Full Band
Rated RF Output Power		10-35 Watts	10-50 Watts 25-100 Watts	10-50 Watts 10-50 Watts
Frequency Stability (-30°C to +60°C, +25°C Reference)		±.00005%	±.00005%	±.00005% ±.00005%
Modulation Limiting		±5/4/2.5 KHz	±5/2.5 KHz	±5/2.5 KHz ±5/2.5 KHz
Emissions (Conducted and Radiated)		-75 dB	-75 dB	-75 dB -75 dB
Audio Response		+1, -3 dB	+1, -3 dB	+1, -3 dB +1, -3 dB
FM Hum & Noise	700 MHz 800 MHz	-45 dB	-45 dB	-45 dB -45 dB
Audio Distortion	700 MHz 800 MHz	1.25%	1.25%	1.25% 1.25%

GPS Specifications

Channels	50
Tracking Sensitivity	<-155 dBm
Accuracy	<6 meters (95%)
Cold Start	<32 seconds (95%)
Hot Start	<1 second (95%)
Mode of Operation	Autonomous (Non-Assisted) GPS

Signaling

Signaling Rate	9.6Kbps(FDMA) / 12Kbps(TDMA) / 1.2Kbps (MDC)
Digital ID Capacity	16,777,216 (Conventional and Trunking)
Network Access Codes	4096 per TIA 102
Project 25 Talk Group IDs	65,535 (Conventional and Trunking)
Error Correction	Soft Decision, Golay, BCH, Reed-Solomon
Modulation	FM, C\$FM, C-QPSK, H-CPM, H-DQPSK



Standard Control Head

- ▶ Full Color Touch screen
- ▶ 5 Line display: Status Icons, three customized display lines of 14 characters, 4 programmable touch keys and menu touch key
- ▶ 3 x 4 Keypad microphone with navigation keys and 3 programmable function keys
- ▶ Dash and Remote Mount Configurations
- ▶ Multiple Control Heads supported: Single, dual and triple allow full control of the transceiver from multiple positions
- ▶ Dual 15 watt external speak outputs per control head

KNG Mobile Military Standards C,D,E, F, & G

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc. /Cat.	Method	Proc. /Cat.	Method	Proc. /Cat.	Method	Proc. /Cat.	Method	Proc. /Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I, II
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I, II
Temperature Shock	503.1	—	503.2	I/A1C3	503.3	I/A1C3	503.4	—	503.5	I (D)
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I (A1)
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	—	507.5	—
Salt Fog	509.1	—	509.2	—	509.3	—	509.4	—	509.5	—
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I, II
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I(4), II
Shock	516.2	I, II	516.3	I, IV	516.4	I/IV	516.5	I, IV	516.6	I, II, V, VI

Dimensions

	Inches	Millimeters
Mid Power Transceiver	2.5 x 6.5 x 8.5	63.5 x 165.1 x 215.9
High Power Transceiver	2.5 x 6.5 x 8.5	63.5 x 165.1 x 215.9
Remote Control Head	2.5 x 6.5 x 1.5	63.5 x 165.1 x 38.1
Mid/High Power Transceiver Weight	7.5 lbs	3.4 kg

Encryption

Supported Algorithms	AES-256, AES-128, DES-OFB, DES-CFB, ADP
Algorithm Capacity	Unlimited
Encryption Keys	1024 Storage Location Number (SLN)/Common Key Reference (CKR)
Frame Re-sync Interval	P25 Common Air Interface 300 mS
Keyloading	IAW TIA-102_AACD (KVL-3000/4000)
Synchronization	OFB- Output Feedback or CFB- Cyber Feedback
Vector Generator	National Institutes of Standards
Type	Digital Encryption
Key Storage	Programmable Volatile / Non-Volatile
Key Erasure	Keyboard Command and KMF
Standards	FIPS-140-2 Level 2 FIPS 197

Transmitter Certifications

700/800 MHz (FCC/IC)	K95KNG9800C / 2116A-KNGP800C
VHF (FCC/IC/JF-12/NTIA)	K95KNGP150 / 2116A-KNG-P150 / JF12-09552 / SPS-18031
UHF Range 1 (FCC/IC/JF-12/NTIA)	K95KNGP400 / 2116A-KNG-P400 / JF12-09552 / SPS-18031
UHF Range 2 (FCC/IC)	K95KNGP500 / 2116A-KNG-P500

Other Certifications

P25 Compliance Assessment (P25CAP) Performance	Trunked and Conventional Performance Class A
P25 Compliance Assessment (P25CAP) Interoperability	Motorola, Harris, EF Johnson, Airbus, Daniels
Intrinsically Safe	Intrinsically Safe (IS) Class I/II/III, Division 1, Groups D, F, G