

# BKR SERIES MULTI-UNIT CHARGER SPECIFICATION SHEET



## BKR Series 6-Bay Desktop Charger

The rugged design stands up to the critical demands of first responders. The BKR0300-6 has six pockets to accommodate any combination of the BKR0100, BKR0101, BKR0102, combined with the BKR 5000 or BKR 9000 radios. Each pocket has an insert to assist charging the BKR0102 battery by itself.



BKR SERIES 6-BAY CHARGER (BK PART NUMBER BKR0300-6)

## System Specifications

	<b>BKR0300-6</b>
Supported Batteries	BKR0100, BKR0101, BKR0102 Li-Ion/Li-Poly: constant voltage, temperature controlled Redundant algorithms provide safety even with a known defective battery. Incorrect battery voltage, mismatched cell and temperature extremes halt the charge by alerting the user with a Red Fail Light. This feature protects the battery and charger.
Temperature	Operating: 0°C-40°C (32°F-104°F) Storage: -40°C-70°C (-40°F-158°F)
Electrical	90-264VAC, 47-63Hz, Fuse: T2.0A, 250VAC
Charge Time	Sequential charging, each battery 4-6 hrs
Charge	Li-Ion: constant voltage, temperature controlled
Length	9.5" (242 mm)
Width	17.5" (445 mm)
Height	3.5" (89 mm)
Weight	7.0 lbs (3.3 kg)