



BKR Series Multi-Unit Charger Specifications



BKR Series 6-Bay Desktop Charger

The rugged design stands up to the critical demands of first responders. The BKR0300-6 has six pockets to accommodate any combination of the BKR0100, BKR0101, BKR0102, combined with the BKR 5000 or BKR 9000 radios. Each pocket has an insert to assist charging the BKR0102 battery by itself.

BKR0300-6

Supported
Batteries

System Specifications

BKR0100, BKR0101, BKR0102

Li-Ion/Li-Poly: constant voltage, temperature controlled

Redundant algorithms provide safety even with a known defective battery. Incorrect battery voltage, mismatched cell and temperature extremes halt the charge by alerting the user with a Red Fail Light. This feature protects the battery and charger.

Temperature

Operating: 0°C-40°C (32°F-104°F)

Storage: -40°C-70°C (-40°F-158°F)

Electrical

90-264VAC, 47-63Hz, Fuse: T2.0A, 250VAC

Charge Time

Each battery 4-6 hrs

Charge

Li-Ion: constant voltage, temperature controlled

Length

9.5" (242 mm)

Width

17.5" (445 mm)

Height

3.5" (89 mm)

Weight

7.0 lbs (3.3 kg)

A photograph of three firefighters in full protective gear running away from the camera down a wet city street at night. The wet pavement reflects the bright orange and yellow lights of emergency vehicles in the distance, creating a dramatic, high-contrast scene. The background is slightly blurred, emphasizing the firefighters in the foreground.

**Mission-Critical Ready.
Hero Tough.™**

**For more information visit
BKTechnologies.com**



800-821-2900
orders@bktechnologies.com
7100 Technology Drive
West Melbourne, FL 32904

bktechnologies.com     